

250 bar



Art.no. **4425**

Manual lever action grease pump, suitable for 18/25 kg - pails. Standard suction tube length 360 mm; can be supplied also in different lengths on demand.

Art.no. **4426**

Similar to art. no. 4425, but with suction tube length 335 mm for 16 kg - pails.

Art. no.	Max outlet pressure	Delivery per stroke	Connections	Weight
4425	250 bar	8 g	1/4" BSP (M)	2 kg
4426				

250 bar



Art.no. **5125**


Portable, manual grease supply kit for 18/25 kg - pails, consisting of:

- Manual lever action grease pump, art. no. 4425;
- Metal drum cover, ø 290 - 330 mm, art. no. 074302;
- Vulcanized follower plate, ø 310 - 260 mm, art. no. 4314VU;
- 1.5 m - rubber hose R1T, ø 1/4";
- Ball valve and rigid outlet pipe with 4 - jaws - hydraulic coupler, art.no. 4218.

Art.no. **5125/S**

Portable, manual grease supply kit such as art.no. 5125, but for 16/18 kg - pails with metal drum cover art.no. 4301, ø 240 - 283 mm, and follower plate art.no. 4311, ø 275 - 230 mm.

Art. no.	Max outlet pressure	Delivery per stroke	Connections	Weight	Dimensions (LxWxH) (mm)
5125	250 bar	8 g	1/4" BSP (M)	5 kg	340x340x630
5125/S					



400 bar



Art.no. **5190**

Manual grease supply kit, consisting of metal 16 kg - pail with 2 wheels, pedal action pump, follower plate, ø 230 mm, art. no. 07 5131, 1.5 m - rubber hose R2AT, ø 1/4", ball valve and rigid outlet pipe with 4 - jaws - hydraulic coupler.

It is possible to obtain different pressure and flow values by changing the position of the pedal.



Art. no.	Pedal position	Max outlet pressure	Delivery per stroke	Connections	Weight	Dimensions (LxWxH) (mm)
5190	1	300 bar	5 g	M 1/4" BSP	22.5 kg	395x553x1069
	2	400 bar	3 g			

