


Art.no. **6561**

Pneumatic rotary vane pump for petrol transfer, self-priming, with aluminium motor, cast iron body and sintered steel rotor.
The pump is supplied with an earth cable to enable an electrostatic discharge.

It is constructed in accordance with directive ATEX 2014/34/EU.



Art. no.	Compressed air supply	Max outlet pressure	Max delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6561	2 – 6 bar	0.5 bar	30 l/min	3/4" BSP (F)	2.5 kg	165x165x180




Art.no. **6930**

Pneumatic 1:1 – piston pump, suitable for the suction and the transfer of petrol.
The pump is supplied with an earth cable to enable an electrostatic discharge.

It is constructed in accordance with directive ATEX 2014/34/EU.



Art. no.	Compressed air supply	Max outlet pressure	Max delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6930	2 – 6 bar	6 bar	25 l/min	3/4" BSP (F)	8 kg	530x120x90



Art.no. **6931**

Electric, selfpriming 12 VDC – rotary vane pump (on demand also available in 230 VAC) for the transfer of petrol, with painted body in cast iron with anticorrosive coating, anti-noise filter (electromagnetic compatibility EMC), thermal protection, non-return valve, pressure relief valve, built-in bypass valve.

The pump is constructed in accordance with directive ATEX 2014/34/EU – IECEx (group II – category 2 – G Ex d IIA T4 Gb).



Art. no.	Voltage	Power	Delivery	Current drain	Connection threads	Weight	Dimensions (LxWxH) (mm)
6931	12 VDC	250 W	50 l/min	21 A	1" BSP (F)	7 kg	195x355x270

