

Waste fluids storage tanks, made in plastic or in steel, compliant with the valid norms regulating the storage of waste fluids (Italian directive 392/96 according to European directives 75/349 EEC and 87/101 EEC).

Art.no. **7008 - 300 l**
 Art.no. **7009 - 260 l**
 Art.no. **7010 - 500 l**



Waste oil storage tank, with double wall in polyethylene (one internal in contact with the oil and one external which serves as a spill containment and security container for the internal one).

The tank is equipped with a wide dome with raisable cover. In its interior there is a removable basket for the drain of oil filters and the opening for charging and discharging the tank.

At the rim of the dome a mechanical level gauge is installed that permits the control of the filling level and a transparent indicator on the side of the external tank allows to detect eventual leakages of the internal tank immediately.

The tank is available in different colours for the storage of different liquids, such as mineral oils, vegetable oils, break fluid, oil-based emulsions or antifreeze.

Art.no.	Capacity (l)	Weight (Kg)	Dimensions (LxWxH) (mm)
7008	300	26	820x820x1080
7009	260	23	800x800x1170
7010	500	37	960x960x1240



Art.no. **8218**

Storage tank for the external use, made of first class carbon steel, equipped with:

- spill containment tray in painted steel with a collection capacity of 100 % of the tank content,
- stable, anti-slip tray base,
- dome with \varnothing 400 mm, including connections,
- external finishing with anti-rust priming and gloss finish.



OPTIONAL
 Galvanized porch roof.

Art.no.	8218/1100	8218/1500	8218/2200	8218/3000
Capacity (m ³ - l)	1.1 - 1100	1.5 - 1500	2.2 - 2200	3 - 3000
External diameter storage tank (mm)	950	1100	1100	1430
Total length (mm)	1650	1650	2400	2300
Width spill containment tray (mm)	1200	1400	1400	1500
Length spill containment tray (mm)	2000	2000	2700	2500
Height spill containment tray (mm)	500	550	600	850

Art.no. **8218/I**

Horizontal, cylindrical double wall tanks for underground storage of flammable and non-flammable liquids. Made with first class carbon steel with dished ends and a 4 mm wall thickness:

- the external wall of the tanks have a protection coating against corrosion with reinforced fiberglass and are undergoing a high voltage test to prove their integrity;
- with overfill protection valve preset on 90% fill level;
- provided with two sockets for the leak detection system;
- with welded shaft and impermeable manhole access, dimensions 800 x 800 x 500 mm (shaft cover not included);
- equipped with metrical level measurement stick or mechanical level indicator;
- other accessories available on demand.



Art.no.	Capacity (l)	Internal diameter (mm)	External diameter (mm)	Total Length (mm)
8218/1000I	1.000	900	1.000	1.780
8218/2000I	2.000	1.270	1.350	1.780
8218/3000I	3.000	1.430	1.500	2.050
8218/4000I	4.000	1.270	1.350	3.260
8218/5000I	5.000	1.430	1.500	3.310
8218/6000I	6.000	1.600	1.700	3.310
8218/8000I	8.000	1.800	1.900	3.440
8218/10000I	10.000	2.000	2.100	3.500