

55 l/min

Art.no. **6435**

Electric vane pump, selfpriming, 230 VAC, for the transfer of diesel. Rotor in sintered steel and vanes in acetal resin. The pump has a built-in bypass valve; protection category IP 55. Delivery 55 l/min.



Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6435	230 VAC	370 W	1.5 A	2800	55 l/min	1" BSP (F)	7 Kg	170x190x230



65 l/min

Art.no. **6218**
Art.no. **6219**

Electric vane pump, selfpriming, 230 VAC or 400 VAC, for the transfer of diesel. Rotor in sintered steel and vanes in acetal resin. The pump has a built-in bypass valve; protection category IP 55. The low number of rotations of the motor permits a constant flow without turbulences, a low noise and less abrasion of the components. Delivery 65 l/min at 900 rpm.



Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6218	400 VAC	550 W	2.5 A	900	65 l/min	1" BSP (F)	15 Kg	200x240x300
6219	230 VAC	700 W	6.2 A					



98 l/min

Art.no. **6220**

Electric vane pump, selfpriming, 230 VAC, for the transfer of diesel. Rotor in sintered steel and vanes in acetal resin. The pump has a built-in bypass valve; protection category IP 55. Delivery 98 l/min at 1400 rpm.



Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6220	230 VAC	550 W	6.2 A	1400	98 l/min	1" BSP (F)	15 Kg	200x240x300

