


Electric and pneumatic selfpriming pumps, with pump body in stainless steel and PTFE – or Viton® gaskets, for the supply of fluids with particular chemical characteristics. It is recommended to check the compatibility of the fluid with the materials of the wetted pump components before use.

Art.no **1058**

Pneumatic, selfpriming rotary gear pump for the transfer of various fluids. Pump body in stainless steel AISI 304, gears in plastic, gaskets in Viton® and pump shaft in stainless steel. Ideal for spraying applications or for keeping a circulation of a fluid in a closed circuit, f. ex. in parts washers.



Art. no.	Compressed air supply	Air consumption	Outlet pressure	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
1058	4 bar	200 l/min	4 bar	10.5 l/min	3/8" BSP (F)	1.5 Kg	165x160x80




Art.no **1052**
 Art.no **1053**
 Art.no **1054**
 Art.no **1055**
 Art.no **1056**

Electric gear pump, selfpriming, 12 VDC, 24 VDC or 230 VAC, particularly suitable for the use of chemical fluids or in applications where the use of wetted parts in stainless steel is required. Resistant to most acid and alkaline solutions. Suitable also for the transfer of battery acid. Includes an in-line filter. Body and shaft in stainless steel AISI 316, gears in PTFE, gaskets in elastomeric fluorine.



Art. no.	Voltage	Current drain	Outlet pressure	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
1052	12 VDC	5 A	1.5 bar	14 l/min	3/8" BSP (F)	1.5 kg	165x160x80
1053			4 bar	12 l/min		1.9 kg	192x170x103
1054	24 VDC	3 A	1.5 bar	14 l/min		1.5 kg	165x160x80
1055			4 bar	12 l/min		1.9 kg	192x170x103
1056	230 VAC	0.8 A	6 bar	10 l/min		7.5 kg	279x166x192



Art.no **1064**
 Art.no **1065**
 Art.no **1066**

Pneumatic double diaphragm pump.
 Pump body and seats in stainless steel AISI 316, diaphragms in Hytrel® + PTFE.
 Selfpriming up to 5 m suction lift, working also unlimitedly in dry running condition.

The pump is constructed in accordance with directive ATEX.

EX II 3/3 GD C IIB T 135° C

Art. no.	Max flow rate	Max. suction lift	Compressed air supply	Connections compressed air inlet	Connections fluid inlet - outlet	Consumption compressed air	Weight	Dimensions (LxWxH) (mm)
1064	55 l/min	6 m	2-7 bar	1/4" BSP (F)	1/2" BSP (F)	200 l/min	5 Kg	238x156x250
1065	120 l/min			3/8" BSP (F)	3/4" BSP (F)	250 l/min	6 Kg	258x178x280
1066	170 l/min			1/2" BSP (F)	1" BSP (F)	350 l/min	20 Kg	360x220x370

