

STANDARD VERSION

400 SERIES - S1 Ø Disc 434 mm - Spool 130 mm - Drum 250 mm



	Art.no. 12 Vdc	Art.no. 24 Vdc	Art.no. ID HYDRAULIC	Art.no. PNEUMATIC	Max. pressure joint	Connection threads IN - OUT	Max diameter hose	Max length hose (m)	Swivel joint*
PAINTED STEEL	SF1242130	SF2442130	SFID42130	SFPN42130	600 bar **	1/2"(M) 1/2"(F)	1/4"	40	9951
							3/8"	25	
							1/2"	18	
	SF1242131	SF2442131	SFID42131	SFPN42131	100 bar	1"(M)-3/4"(F)	3/4"	12	9986
							1"	8	
AISI 304 STAINLESS STEEL	SX1242130	SX2442130	SXID42130	SXPN42130	200 bar **	1/2"(M) 1/2"(F)	1/4"	40	9963
							3/8"	25	
							1/2"	18	
	SX1242131	SX2442131	SXID42131	SXPN42131	100 bar	1"(M)-3/4"(F)	3/4"	12	9986
							1"	15	

400 SERIES - S2 Ø Disc 434 mm - Spool 195 mm - Drum 250 mm

	Art.no. 12 Vdc	Art.no. 24 Vdc	Art.no. ID HYDRAULIC	Art.no. PNEUMATIC	Max. pressure joint	Connection threads IN - OUT	Max diameter hose	Max length hose (m)	Swivel joint*
PAINTED STEEL	SF1242190	SF2442190	SFID42190	SFPN42190	600 bar **	1/2"(M) 1/2"(F)	1/4"	50	9951
							3/8"	40	
							1/2"	30	
	SF1242191	SF2442191	SFID42191	SFPN42191	100 bar	1"(M)-3/4"(F)	3/4"	18	9986
							1"	12	
AISI 304 STAINLESS STEEL	SX1242190	SX2442190	SXID42190	SXPN42190	200 bar **	1/2"(M) 1/2"(F)	1/4"	60	9963
							3/8"	40	
							1/2"	30	
	SX1242191	SX2442191	SXID42191	SXPN42191	100 bar	1"(M)-3/4"(F)	3/4"	18	9986
							1"	12	

400 SERIES - S3 Ø Disc 434 mm - Spool 260 mm - Drum 250 mm

	Art.no. 12 Vdc	Art.no. 24 Vdc	Art.no. ID HYDRAULIC	Art.no. PNEUMATIC	Max. pressure joint	Connection threads IN - OUT	Max diameter hose	Max length hose (m)	Swivel joint*
PAINTED STEEL	SF1242260	SF2442260	SFID42260	SFPN42260	600 bar **	1/2"(M) 1/2"(F)	1/4"	60	9951
							3/8"	50	
							1/2"	40	
	SF1242261	SF2442261	SFID42261	SFPN42261	100 bar	1"(M)-3/4"(F)	3/4"	20	9986
							1"	15	
AISI 304 STAINLESS STEEL	SX1242260	SX2442260	SXID42260	SXPN42260	200 bar **	1/2"(M) 1/2"(F)	1/4"	60	9963
							3/8"	50	
							1/2"	40	
	SX1242261	SX2442261	SXID42261	SXPN42261	100 bar	1"(M)-3/4"(F)	3/4"	20	9986
							1"	15	



*) The reels in painted steel are equipped with mineral oil compatible swivel joint gaskets. The hose reels in stainless steel come with water-compatible Viton® swivel joint gaskets. See pages 263-265 for the complete range of swivel joints with gaskets compatible with other liquids.

**) When ordering, specify whether or not the application implies the use of low pressure hoses (see page 266 regarding the splitting of the roller).

DIMENSIONS AND PACKAGING

Art.no.	D (mm)	F (mm)	E (mm)	A-B-C (mm)	Packaging dimensions (mm)	Weight (kg)
S1	434	130	250	358x544x538	670x800x900	23
S2	434	195	250	426x544x538	670x800x900	26
S3	434	260	250	491x544x538	670x800x900	28