

Complete mobile pneumatic grease supply kits, suitable for 180 kg – drums in any kind of inside or outside use.
Max pressure achievable: 400 bar.



Art.no. **4990C**

Mobile pneumatic grease supply kit for 180 kg - drums, consisting of:

- Pneumatic grease pump, art. no. 4080;
- Pressure regulator and air filter with moisture separator, art. no. 7180;
- 3 m – high pressure hose SAE 100 R2 AT, 1/4", art. no. 4503;
- High pressure grease control gun, 300 mm – steel braid outlet hose Ø ext. 10 mm and 4 - jaws - hydraulic coupler, art. no. 4205;
- High pressure Z – swivel, art. no. 4221;
- Vulcanized follower plate, ø 590 - 540 mm, art. no. 4319VU;
- Metal drum cover, ø 600 – 560 mm, art. no. 4308;
- Trolley with 4 wheels, art. no. 4380.

Art.no. **4990**

Mobile pneumatic grease supply kit such as art. no. 4990C, but without art. nos. 7180 and 4221.

Art. no.	Max outlet pressure	Delivery	Connection compressed air	Compressed air supply	Weight	Dimensions (LxWxH) (mm)
4990C	400 bar	2400 g/min	1/4" BSP (F)	2 - 8 bar	22 kg	900x830x1400



Art.no. **4910**

Mobile pneumatic grease supply kit for 180 kg - drums, consisting of:

- Pneumatic grease pump, art. no. 4080;
- Pressure regulator and air filter with moisture separator, art. no. 7180;
- Open hose reel, art. no. 9016;
- 15 m – high pressure hose SAE 100 R2 AT, 1/4", art. no. 4515;
- 2 m – connection hose SAE 100 R2 AT, 1/4", art. no. 4502;
- High pressure grease control gun, 300 mm – steel braid outlet hose Ø ext. 10 mm and 4 - jaws - hydraulic coupler, art. no. 4205;
- Vulcanized follower plate, ø 590 - 540 mm, art. no. 4319VU;
- Metal drum cover, ø 600 – 560 mm, art. no. 4308;
- Trolley with 4 wheels and mounting bracket for hose reel, art. no. 4385.

Art. no.	Max outlet pressure	Delivery	Connection compressed air	Compressed air supply	Weight	Dimensions (LxWxH) (mm)
4910	400 bar	2400 g/min	1/4" BSP (F)	2 - 8 bar	72 kg	900x870x1400



Art.no. **4911**

Mobile pneumatic grease supply kit for 180 kg - drums, consisting of:

- Pneumatic grease pump, art. no. 4080;
- Pressure regulator and air filter with moisture separator, art. no. 7180;
- Open hose reel, art. no. 9016;
- 15 m – high pressure hose SAE 100 R2 AT, 1/4", art. no. 4515;
- 2 m – connection hose SAE 100 R2 AT, 1/4", art. no. 4502;
- High pressure grease control gun, 300 mm – steel braid outlet hose Ø ext. 10 mm and 4 - jaws - hydraulic coupler, art. no. 4205;
- High pressure Z – swivel, art. no. 4221;
- Vulcanized follower plate, ø 590 - 540 mm, art. no. 4319VU;
- Metal drum cover, ø 600 – 560 mm, art. no. 4308;
- Heavy duty trolley with 4 wheels and grate, art. no. 4389.

Art. no.	Max outlet pressure	Delivery	Connection compressed air	Compressed air supply	Weight	Dimensions (LxWxH) (mm)
4911	400 bar	2400 g/min	1/4" BSP (F)	2 - 8 bar	90 kg	900x1030x1400