

OIL PROFESSIONAL Model



Electric gear pump, self-priming, for the supply of oil under demanding conditions at medium pressure and with long pumping distances; guarantees a constant flow and delivery, even after long pumping distances or with simultaneous supplies.

Available with motors in 230 VAC, 400 VAC and 110 VAC.

Models 6135 and 6138 are also available in the 60 Hz version (art.no. **6135/60** and art.no. **6138/60**)

Includes a bypass valve preset on 28 bar pressure.

Electric cable with plug not included.



Art. no.	Voltage	Power	Current drain	Rpm	Outlet pressure	Delivery	Connections IN - OUT	Weight	Dimensions (LxWxH) (mm)
6133	230/400V - 50 Hz	2,2 kW	8 A	2870	28 bar	30 l/min	1" BSP (F) 1" BSP (F)	28 kg	450x180x250
6135	230 V - 50 Hz		14.6 A	1300					
6135/60	230 V - 60 Hz		14.6 A	1300					
6138	230/400V - 50 Hz		9 A	1400					
6138/60	230/400V - 60 Hz		8.3 A	1680					
6149	230/400V - 50 Hz		8 A	2870	10 bar	52 l/min		32 kg	

Performance values are based upon the following test conditions: Hydraulic oil ISO 68 at 22°C - free flow outlet.

KIT PROFESSIONAL



Electric gear pump, art. no. 6135, equipped with kit art. no. 7373 consisting of pressure accumulator, inline oil filter, non-return valve, manometer, connection adapters and an electronic pressure switch that starts the pump once the control gun is activated and stops it again due to the pressure increase in the circuit once the gun is closed. The pressure accumulator guarantees a constant oil flow by avoiding continuous starts and stops of the motor that could cause damages in case of dispensing small quantities.



Includes a bypass valve preset on 28 bar pressure.

Electric cable with plug not included.

Art. no.	Voltage	Power	Current drain	Rpm	Outlet pressure	Delivery	Connections IN - OUT	Weight
6136	230 VAC - 50 Hz	2.2 kW	15 A	1400	28 bar	30 l/min	1" BSP (M) 1" BSP (M)	33 kg

Performance values are based upon the following test conditions: Hydraulic oil ISO 68 at 22°C - free flow outlet.

KIT CARENATO



Kit 3049

Enclosed oil supply kit, composed of: electric gear pump, art. no. 6136, metal and lockable cabinet, art. no. 7376, and safety switch of protection category IP 55, art. no. 7370/2, with 3 m - cable and plug.



Kit 3050

Enclosed oil supply kit, such as art. no. 3049, but including electric gear pump, art. no. 6149, with delivery 52 l/min and safety switch of protection category IP 55, art. no. 7377. Ideal for pipework installations.

Art. no.	Voltage	Power	Current drain	Rpm	Outlet pressure	Delivery	Connections IN - OUT	Weight	Dimensions (LxWxH) (mm)
3049	230 VAC - 50 Hz	2.2 kW	15 A	1400	28 bar	30 l/min	1" BSP (M) 1" BSP (M)	37 kg	600x500x300
3050	400 VAC - 50 Hz		10 A	2760	10 bar	52 l/min	1" BSP (M)	39 kg	

Performance values are based upon the following test conditions: Hydraulic oil ISO 68 at 22°C - free flow outlet.